



Low Noise
68 dB(A)

ATEX-40L (4W)

- Legally Certified Explosion Proof/Ignition Proof.
- Less than 10 Ohms of resistivity.
- HEPA Filter - Efficiency of 99.995% on 0.3 micron. Tested IEST RP-CC001.3. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA Vacuum Cleaners are Aerosol Leak tested before leaving our facility.
- Cleanroom compatible with ISO Class 4 (former Class 10). (Can be used in the pharmaceutical industry)
- For general cleanup in Hazardous Locations.
- For Dry Recovery only.
- All Stainless Steel SAE 304 construction.
- Mounted on a SD 4-Wheel Dolly. (Dolly and Cart have SD Conductive wheels)
- Includes a complete Static Dissipative Toolkit.

Class I - Division 1 - Groups A, B, C and D T6

Class II - Division 1 - Groups E, F and G

Hazardous Locations as defined in the National Electric Code (NFPA 70)



ATEX 3rd PARTY CERTIFIED
CE 0081 II 2 GD c IIC T6 (85 °C)
LCIE 03 ATEX 6310

PNEUMATICALLY (AIR) OPERATED

ATEX CATEGORY 2 GD - IECEx EPL Gb and Gc

Db and Dc - GAZ GROUP IIC AND DUST GROUP IIIC

ESD FREE DESIGNED TO PREVENT IGNITION HAZARDS.

WE USE METAL PARTS OR STATIC DISSIPATIVE POWDER COATING TO PREVENT ELECTROSTATIC DISCHARGE (ESD)



EXPLOSION
PROOF



LESS THAN
10 OHMS



HIGH
EFFICIENCY



PHARMA
APPLICATIONS



DRY
RECOVERY



HEPA
INCLUDED



STAINLESS STEEL
AISI 304



STATIC
DISSIPATIVE

VENTURI	SINGLE
MINIMUM COMPRESSOR	15 HP
AIR LINE SIZE (DIAM.)	0.5 in.
REQUIRED INPUT AIR VOLUME	35-45 CFM
REQUIRED INPUT AIR PRESSURE	80 PSI
AIR FLOW	110 CFM
VACUUM PRESSURE	110 in. H ₂ O
RECOVERY CAPACITY	10 Gal. (38L)
NOISE LEVEL	68 dB(A)

** SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Use only recommended tools and accessories



INCLUDED - STATIC DISSIPATIVE TOOLKIT