



EXP1-40L (4W)

- Legally Certified Explosion Proof/Ignition Proof.
- Less than 10 Ohms of resistivity.
- HEPA Filter Efficiency of 99.995% on 0.3 micron.
 Tested IEST RP-CC001.3. H14 by MPPS method as per
 EN 1822 and OSHA compliant. All of our HEPA
 Vacuum Cleaners are Aerosol Leak tested before
 leaving our facility.
- · Electrically operated.
- Cleanroom compatible with ISO Class 4 (former Class 10). (Can be used in the pharmaceutical industry)
- For general cleanup in Hazardous Locations.
- Single Phase Explosion Proof/Dust Ignition Proof motor.
- For Dry Recovery only.
- All Stainless Steel SAE 304 construction.
- Mounted on a SD 4-Wheel Dolly. (Dolly and Cart have SD Conductive wheels)
- Includes a complete Static Dissipative Toolkit.



CLASS I · DIVISION 1 · GROUP D T3C CLASS II · DIVISION 1 · GROUPS E, F and G



ATEX 3rd PARTY CERTIFIED



C ∈ 0081 II 2 GD Ex d IIA T3 Gb Ex T IIIC T200°C Db IP6x LCIE 03 ATEX 6297

SINGLE PHASE 1.3HP CSA® (NRTL) Certified

OSHA Combustible Dust (NEP) NATIONAL EMPHASIS PROGRAM Approved

EXPLOSION PROOF/DUST IGNITION PROOF CSA® CERTIFICATE #1032222



N LESS THAN 10 OHMS



PHARMA APPLICATIONS

HEPA HEPA INCLUDED

AISI 304

STAINLESS STEEL



EL n

STATIC

TYPE	ELECTRIC
TEFC	YES
HERTZ	50 Hz / 60 Hz
CURRENT (MAX)	9 amps
PHASE	SINGLE
VOLTAGE @ 60Hz	120 V · (50 Hz / 60 Hz)
POWER @ 60Hz	1.3 HP
SUCTION INLET	2 in.
WATTAGE	1000 W
AIRFLOW - BLOWER (MAX)	132 CFM (224 M ³ /H)
VACUUM PRESSURE	69 in. H ₂ O (1752.6 mm H ₂ O)
DRY RECOVERY	10.5 Gal. (40L)
ELECTRICAL PLUG (MIN. AMP)	NOT INCLUDED
SOUND LEVEL @ 1m	78 dB(A)
CORD LENGTH	50 ft.
CART TYPE	4-Wheel Dolly

^{**} SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE

Use only recommended tools and accessories





T. (514) 702-9383 E. dutyvac@gmail.com W. www.dutyvac.net